

Technical Data Sheet

Ceiling Pro 5 in 1

Performance Characteristics

- **Seals, primes, block stains finishes & bridges cracks**
- **Water Based**
- **Low Tension**
- **Cationic**
- **Flat white finish – non yellowing**
- **1 hour recoat**

Zinsser Ceiling Pro 5 in 1 is based on ground-breaking paint technology that effortlessly provides a perfectly finished ceiling every time. It adheres to any surface, seals stains (including water and smoke stains), primes and finishes whilst bridging hairline cracks.

In addition Ceiling Pro 5 in 1 contains a biocide that protects the dried coating against fungal degradation, prolonging the life of your painted ceiling. These outstanding features combine with a 1 hour recoat time, low odour and ultra low VOC content.

Preparation: Ensure surfaces are clean, dry and free of any contamination. Remove any existing mould or mildew before painting. Any excessive dusting of new surfaces should be removed prior to painting. Ensure surface has moisture content of less than 15%. Exposed nail heads should be countersunk and filled before coating with **ZINSSER CEILING PRO 5-IN-1**.

Application: Stir thoroughly before use. **ZINSSER CEILING PRO 5-IN-1** can be applied by brush, roller or airless spray. If spraying use tip size 0.015" - 0.019" at 2000 – 2500 psi. For brush and roller no thinning is required. If spraying, **ZINSSER CEILING PRO 5-IN-1** may be thinned up to 5% with clean water.

Coverage: 10m² per litre per coat. Two coats may be required when covering dark surfaces or stubborn stains.

Drying: Touch dry – 30 mins. Recoat – 1 hour (at 20°C).

Clean Up: Remove as much **ZINSSER CEILING PRO 5-IN-1** as possible from application equipment before washing with water. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

Limitations: **ZINSSER CEILING PRO 5-IN-1** will not mix with conventional emulsion paints, ensure application equipment is thoroughly clean before use. Only apply when air temperature is between 10° and 30°C. Not suitable for application to bare ferrous metal.

Spread rate: 10m²/L

Volume Solids: 40%

Typical film thickness per coat: 40 micron

Density: 1.45

VOC: 5g/L

Shelf life: 2 years in unopened containers

Storage: Store indoors at 5-25°C. Protect from frost.

Finish: Matt

Touch Dry at 20°C: 30 mins

Hard Dry at 20°C: 4 hours

Recoat at 20°C: 1 hour

Drying and recoat times may be extended at lower temperature and high humidity.